

PERMANENT OVERLAY

Description

Series ORALITE® 5051 TRANSPARENT FILM are transparent coloured, high-performance cast films on the basis of a PVC polymer blend. The material features excellent transparency, outstanding dimensional stability and optimum cutting and processing properties. It is guaranteed that the colour-laminates of the series ORALITE® 5051 TRANSPARENT FILM on the white reflective films of the ORALITE® 5700 / 5710 ENGINEER GRADE fulfill the requirements of the international specifications of this class such as EN 12899-1 (European Regulation), DIN 67520 and DIN 6171 (Germany), BS 873: Part 6 (Great Britain), NFP 98-520 (France), SN 640878 (Switzerland), ASTM D 4956 (US), JIS Z 9117 (Japan) for the specific coefficient of retroreflection and colour coordinates.

Surface

Polymer PVC film

Release paper

Polyester film, silicone coated one side, reverse treated, 0.100 mm (0.004 in)

Adhesive




Solvent polyacrylate, permanent, transparent.

Area of use

ORALITE® 5051 TRANSPARENT FILM has been developed especially as laminate for ORALITE® reflective films. 5051 TRANSPARENT FILM has been especially developed for use on cutting plotters to produce marking and symbols on traffic signs, traffic control and guidance signs, warning and information signs. ORALITE® 5051 TRANSPARENT FILM offers a profitable alternative for screen printing especially when small numbers of a product are required. ORALITE® 5051 TRANSPARENT FILM is suitable for long-term outdoor use.

Resistance to solvents and chemicals

With expert application resistant to most oils, grease, fuels, aliphatic solvents, weak acids, salts and alkalis.

| ORALITE 5051 PRICES | | |
|---|--------------|-------------|
| Colour | 1220mm x 50m | 610mm x 50m |
|  | £671.00 | £335.50 |
|  | £670.00 | £335.50 |
|  | £671.00 | £335.50 |

